



Options:
Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.



**WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!**

Type: DTS-50			Part No. DTS5030 ...			
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
DTS5030.020	200	200	390	50	---	---
DTS5030.025	250	250	380	50	---	50
DTS5030.030	300	300	370	50	---	100
DTS5030.035	350	350	360	50	---	150
DTS5030.040	400	400	350	50	---	200
DTS5030.045	450	450	340	50	---	250
DTS5030.050	500	500	330	50	---	300
DTS5030.055	550	550	320	50	150	---
DTS5030.060	600	600	310	50	175	---
DTS5030.065	650	650	300	50	200	---
DTS5030.070	700	700	290	50	225	---
DTS5030.075	750	750	280	50	250	---
DTS5030.080	800	800	270	50	275	---
DTS5030.085	850	850	260	50	300	---
DTS5030.090	900	900	250	50	325	---
DTS5030.095	950	950	240	50	350	---
DTS5030.100	1000	1000	230	50	375	---
DTS5030.105	1050	1050	220	50	400	---
DTS5030.110	1100	1100	210	50	425	---
DTS5030.115	1150	1150	205	50	450	---
DTS5030.120	1200	1200	200	50	475	---
DTS5030.125	1250	1250	195	50	500	---
DTS5030.130	1300	1300	190	50	525	---
DTS5030.135	1350	1350	185	50	550	---
DTS5030.140	1400	1400	180	50	575	---
DTS5030.145	1450	1450	170	50	600	---
DTS5030.150	1500	1500	160	50	625	---
DTS5030.155	1550	1550	150	50	650	---
DTS5030.160	1600	1600	140	50	675	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam